



secureIT™  
P SERIES



# PLEXIGLAS LIBRARY SECURITY SYSTEM/ANTENNAS

AUTHORIZED US DEALER

**Murphy Security Solutions**

1217 Robinhood Lane, La Grange Park, IL 60526

Call: 1-708-482-4682

[www.murphysecuritysolutions.com](http://www.murphysecuritysolutions.com)



D-Tech's secureIT™ P-series system provides perimeter-based material protection and improves alarm-handling capability for libraries where enhanced protection is required with a concern for the aesthetic environment.

Packaged in a durable Plexiglas frame with attractive stainless steel base, the secureIT™ system combines an obvious deterrent with a stylish design.

## FEATURES

- Compatible with D-Tech 13.56 MHz RFID labels and items tagged with approved labels from book suppliers including multi-vendor reading (MVR), allowing reading of other RFID labels
- D-Tech's advanced digital RFID technology uses state-of-the-art, digitally-enhanced receiver to chip technology to ensure superior detection with false-alarm free protection
- Integrated alarm lights and sounder provide individual-aisle identification through multiplexing
- GateViewer software application collates and identifies all alarm incidents, with connection and troubleshooting status to installed system (RFID version only)
- Mounts as a free-standing unit or on a standard ramp
- Alarm output to recording equipment and/or voice alarms available
- Integrated lights illuminate system for the visually impaired and to indicate that the system is on and working
- Optional integrated people counter

## SPECIFICATIONS

	Antenna Reader	LR200 MUX	Multiplexer	Light option reg
Height	69"	13"	4"	4"
Width	4"	7"	4"	4"
Length	20"	5"	7"	7"
Weight	50lbs	5lbs	1lbs	4lbs

## MATERIALS

Transparent acrylic panel for the frame and lower base is stainless steel

## POWER SUPPLY

110 VAC

One outlet per antenna system electronic-dedicated, clean, grounded power required

15 amp fused outlet

## ELECTRONICS

LR2000 (Feig) – Tagsys multiplexer for larger aisle configurations, light regulator and power unit

## PERFORMANCE

32" - 44" Aisle

## INSTALLATION REQUIREMENTS

- 1 x single aisle system requires two transceiver antennas and one LR2000 RFID power supply and splitter unit.
- Adjustable footplate is included in package for floor fixing and levelling. Conduit moulding or floor cut.

## AFI/EAS

Recommended AFI mode is supported for GateViewer but EAS bit is also supported.

## LOCATION

The system location and layout is to be detailed and decided upon by the D-Tech's Project Manager working in conjunction with the client team.



5803 New Jersey Avenue • Suite 101 • Wildwood Crest • NJ • 08260

1-855-38-DTECH

usainfo@d-techinternational.com

@Dtechdirect

d-techinternational.com

d-techshop.com